

Modelo	BTM-150H
Marca	Encapsulando®
Frecuencia de corte	AL/PL:35 veces/min AL/AL:25 veces/min
Área máxima de formación	140mm x 110mm
Profundidad de de formación máxima	20mm estándar (Personalizable hasta 30mm)
Rango ajustable de carrera	40-120mm (Personalizable)
Presión de aire	0.3-0.6Mpa
Caudal de la bomba de aire	≥0.2m ³ /min
Conexión eléctrica	Personalizable
Potencia total	3.3Kw
Motor Principal	1.1Kw
Potencia calorífica de formación superior e inferior	1.5Kw
Potencia de calor del termosellado	0.7Kw
Película PVC	0.15-0.5*150 (mm)
Película de aluminio PTP	0.02-0.035*150 (mm)
Tamaño del equipo (LxAnxAI)	230cm x 56cm x 160cm
Peso del equipo	Net 620kg
Ruido	<75dBA

Item	Nombre	Cantidad	Modelo	Marca
1	touch screen	1		Siemens
2	PLC	1	CPU224XP	Siemens
3	Thermometer Modules	1	EM 231	Siemens
4	Extension module	1	EM 222	Siemens
5	switching power supply	1	NES-50-24	Beijing
6	Relays	6		Schneider
7	breaker	4	DZ47-60 C10	Schneider
8	breaker	1	DZ47-60 C16	Schneider
9	Solid state relays	3	G3NB-225B-1	China
10	frequency converter	1	1.5KW 460V 3phase M	Omron
11	solenoid valve	7	24V	AirTAC
12	air regulators	1	4000	AirTAC
13	air regulators	1	2000	AirTAC
14	Forming cylinder	1	SU100×35	AirTAC
15	Main motor	1	YE2-90S-4 1.5KW	Jiangsu
16	main gear reducer	1	XWD3-23	Zhejiang
17	Heat sealing cylinder	2	ZYQG100×35	Zhejiang
18	Traction cylinder	1	SDA32×10	AirTAC
19	Motor of feeder	1	Z5D120-220GU 120KW 2800rpm	Zhejiang
20	proximity switch	3		Omron
21	PTP discharge motor	1	4GN-5-K 25W	Zhejiang
22	PVC discharge motor	1	4GN-5-K 25W	Zhejiang
23	Closed waste motor	1	4GN-5-K 25W	Zhejiang
24	Forming heating plate	2	/	Zhejiang
25	Sealing heating plate	1	/	Zhejiang
26	Multi-warning light	1	LTA-205	Zhejiang